

STR 3105	Hybrid-IC		-		**
STR 4090(A)	Hybrid-IC		-		**
STR 4211	Hybrid-IC		-		
STR 5412	Hybrid-Z-IC		=20/5Pin	STR 5412	=20/5Pin
STR 6020	Hybrid-Z-IC		-		**
STR 9005	Hybrid-Z-IC	TV, VC, lo-drop, +5V, 4A, 75W	=20/5Pin		
STR 9012	Hybrid-Z-IC	=STR 9005: +12V	=20/5Pin		
STR 9015	Hybrid-Z-IC	=STR 9005: +15V	=20/5Pin		
STR 9052	Hybrid-Z-IC	=STR 9005: +5,2V	=20/5Pin		
STR 11006	Hybrid-IC		77/5Pin	STR 11006	77/5Pin
STR 20013	Hybrid-Z-IC		-		+
STR 40090	Hybrid-Z-IC		77/5Pin	STR 40090	77/5Pin
STR 41090	Hybrid-Z-IC	Schaltregler/switching reg., +90V	77/5Pin	STR 41090	77/5Pin
STR 41091	Hybrid-Z-IC	Schaltregler/switching reg.	-		**
STR 41115	Hybrid-Z-IC	Schaltregler/switching reg., +115V	-		
STR 54041	Hybrid-Z-IC	Uin=900V, Uo=41,8V	77/5Pin	STR 54041	77/5Pin
STR 58041	Hybrid-IC		77/5Pin	STR 58041	77/5Pin
STR 80145(A)	Hybrid-IC	110/240V Switch Modul, 5A _{max} , Us=145V _{max}	77/5Pin	STR 81145(A)	77/5Pin
STR 81145(A)	Hybrid-IC	110/240V Switch Modul, 10A _{max} , Us=145V _{max}	77/5Pin	STR 81145(A)	77/5Pin
STR 81159(A)	Hybrid-IC	110/240V Switch Modul, 10A _{max} , Us=159V _{max}	77/5Pin	-	
STR 83145	Hybrid-IC	110/240V Switch Modul, 10A _{max} , Us=145V _{max}	77/5Pin	-	
STR 83159	Hybrid-IC	110/240V Switch Modul, 10A _{max} , Us=159V _{max}	77/5Pin	-	
STR 84145	Hybrid-IC	110/240V Switch Modul, 12A _{max} , Us=145V _{max}	77/5Pin	-	
STT 1	UJT-P	30V, I _p <4μA, I _v >7mA, η=0,58...0,64	7b	-	
STTB 506 D	Si-Di	TV-Clamping-Di, 600V, 5A, <95ns	17k	(BY 329/1200)	17k
STTB 506 F	Si-Di	=STTB 506D: Iso	17d	BYR 29F-600	17d
STTB 506 M	Si-Di	=STTB 506D: SMD, A=Pin1...5, K=Base Tab	10-MDIP	-	
STV-2 H-O	Si-St	1,07...1,15V(7mA)	-		
STV-2 H-W	Si-St	1,13...1,21V(7mA)	-		
STV-3-G	Si-St	1,72...1,80V(7mA)	31a	-	
STV-3 H-G	Si-St	1,72...1,80V(7mA)	-		
STV-3 H-O	Si-St	1,60...1,68V(7mA)	-		
STV-3 H-W	Si-St	1,60...1,80V(7mA)	-		
STV-3 H-Y	Si-St	1,66...1,74V(7mA)	-		
STV-3-O	Si-St	1,60...1,68V(7mA)	31a	-	
STV-3-Y	Si-St	1,66...1,74V(7mA)	31a	-	
STV-4 H	Si-St	2,10...2,35V(7mA)	-		
STV 2100	LIN-IC	CTV, Signal-Prozessor, PAL	30-SDIP	-	
STV 2101 A	LIN-IC	CTV, Signal-Prozessor, PAL-Decoder	42-SDIP	-	
STV 2102 A	LIN-IC	CTV, Signal-Prozessor, PAL	42-SDIP	-	
STV 2110 A	LIN-IC	CTV, Signal-Prozessor, PAL	42-SDIP	-	
STV 3300	CMOS-IC	Digital Video Filtering & Dematrixing	52-PLCC	-	
STV 5343	LIN/DIG-IC	Teletext Decoder, RAM-Adress. ...64kB	40-DIP	-	
STV 5343 S	LIN/DIG-IC	=STV 5343: Fig. →	42-SDIP	-	
STV 5345	HCMOS-IC	Teletext-Prozessor f. West-Europa, I°C	40-DIP	-	
STV 5345 H	HCMOS-IC	=STV 5345: f. Ost-Europa	40-DIP	-	
STV 5345 T	HCMOS-IC	=STV 5345: f. Europa + Türkei	40-DIP	-	
STV 5712	LIN-IC	SMD, VC, Audio A/W-Verst./Amp.	16-MDIP	-	
STV 5715	LIN-IC	SMD, VC, 2-Kopf/Head A/W-Verst./Amp.	20-MDIP	-	
STV 5722	LIN-IC	SMD, VC, 2-Kopf/Head A/W-Verst./Amp.	16-MDIP	-	
STV 5726	LIN-IC	SMD, VC, 4-Kopf/Head A/W-Verst./Amp.	20-MDIP	-	
STV 5730	LIN-IC	SMD, TV,VC, On-Screen Display	28-MDIP	-	
STV 8438	D/A-IC	8-Bit Image Proc., 3 Video DACs	42-SDIP	-	
STV 9303	LIN-IC	CTV,TV, VA-System	10-SIL	-	
STV 9303 W	LIN-IC	=STV 9303: Fig. →	11-SILP	-	
STV 9378(F)	LIN-IC	CTV,TV,Monitor, hi-res, VA-E	177/7Pin	-	